

ERECTION INSTRUCTIONS

COLORADO

BEFORE USE

PLEASE TAKE TIME TO READ AND UNDERSTAND THE ERECTION INSTRUCTIONS. FAILURE TO ERECT THE TENT IN ACCORDANCE WITH THE INSTRUCTIONS MAY RESULT IN DAMAGE TO BOTH FABRIC AND POLE SYSTEMS. SUCH DAMAGE CANNOT BE COVERED BY THE WARRANTY.

WARNING!!

DO NOT PUSH TENT PEGS IN BY HAND, ALL TENT PEGS SHOULD BE DRIVEN HOME USING A WOODEN OR RUBBER FACED Mallet OR SIMILAR TOOL.

TO ENSURE MAXIMUM POSSIBLE WATERPROOFING THE MAIN FLY SHEET SEAMS HAVE BEEN TAPED. SHOULD THE TAPE BE DAMAGED AND PEEL AWAY YOU CAN EFFECT A REPAIR BY USING SEAM SEALER AROUND THE PROBLEM AREA.

WE ALSO RECOMMEND THAT SEAM SEALER IS APPLIED TO UNTAPED SEAMS TO PREVENT LEAKAGE.

IT IS IMPORTANT THAT YOU DO NOT ALLOW SEAM SEALER TO CONTAMINATE THE TEETH OF ANY ZIPS, AS THIS WILL PREVENT THE ZIP FROM FUNCTIONING CORRECTLY.

IF YOU DO USE SEAM SEALER IT IS BEST APPLIED WHEN THE TENT IS DRY. PICK A DRY WARM DAY TO CARRY OUT ANY SEALING AND PLEASE ALLOW 48 HOURS FOR THE SEALANT TO CURE PRIOR TO RE-PACKAGING THE TENT.

FAILURE TO ALLOW THE SEALANT TO DRY FULLY PRIOR TO PACKING THE TENT UP WILL STICK THE FABRIC TOGETHER POSSIBLY CAUSING IRREPARABLE DAMAGE.

DURING USE

TENTS CONTAINING A HIGH PROPORTION OF SYNTHETIC MATERIALS ARE SOMETIMES AFFECTED BY CONDENSATION, THIS SHOULD NOT BE CONFUSED WITH LEAKAGE AND CAN USUALLY BE CURED BY ENSURING THAT ADEQUATE VENTILATION IS AVAILABLE BY LEAVING DOORWAYS SLIGHTLY UNZIPPED WHEREVER POSSIBLE.

DO NOT PITCH UNDER TREES, MAKE USE OF NATURAL WIND BREAKS LIKE HEDGES OR WALLS, FACE THE TENT DOOR AWAY FROM THE PREVAILING WIND. USE TWO HANDS WHEN OPENING AND CLOSING ZIPS, THIS WILL HELP PREVENT PREMATURE ZIP FAILURE.

READ AND UNDERSTAND THE FIRE PRECAUTIONS INFORMATION ATTACHED TO THE INSIDE OF THE TENT.

CARE OF YOUR TENT *WARNING!!*

TENT FABRICS CAN BE WEAKENED BY PROLONGED EXPOSURE TO SUNLIGHT, UNDER NORMAL HOLIDAY USE YOUR TENT WILL GIVE YOU LONG SERVICE BUT ERECTION FOR EXTENDED PERIODS IN STRONG SUNLIGHT WILL CAUSE DETERIORATION.

IF YOU ARE LIKELY TO USE YOUR TENT FOR PROLONGED PERIODS IT WOULD BE WISE TO USE A SITE, WHICH IS A SHADED AS POSSIBLE.

TENTS ARE BEST STORED OPENED OUT, IF THIS IS NOT POSSIBLE AIR FULLY AND ENSURE IT IS TOTALLY DRY BEFORE PACKING IT AWAY AT THE END OF YOUR HOLIDAY.

STORE YOUR TENT IN A WELL VENTILATED DRY PLACE. LOOK AFTER YOUR TENT AND IT WILL LOOK AFTER YOU.

HAVE ANY DAMAGE TO YOUR TENT REPAIRED AT FIRST OPPORTUNITY. FAILURES IN FIBERGLASS POLES NORMALLY OCCUR THROUGH INCORRECT USE, MAKE SURE THE POLE SECTIONS ARE FULLY INSERTED INTO THEIR ADJOINING FERULES AND DO NOT OVER STRESS THE POLE BEYOND IT'S DESIGNED CURVE. ZIPS SHOULD BE TREATED WITH CARE TO PREVENT PREMATURE FAILURE AND THE TENT SHOULD BE KEPT CLEAN AND DRY AFTER USE.

INSURANCE

WE HIGHLY RECOMMEND THAT YOUR TENT BE INSURED AGAINST THEFT AND STORM OR ACCIDENTAL DAMAGE. STORM OR ACCIDENTAL DAMAGE IS NOT COVERED BY THE WARRANTY.

CHECK YOUR EQUIPMENT BEFORE GOING AWAY WITH YOUR TENT. ENSURE THAT YOU ARE FAMILIAR WITH THE PITCHING OF THE TENT AND THAT ALL PARTS ARE PRESENT.

YOU SHOULD FAMILIARIZE YOURSELF WITH THE TENT, INCLUDING ANY LIMITATIONS THAT IT MAY HAVE FOR YOUR PARTICULAR USE.

DOMES ARE PORTABLE STRUCTURES WHICH UNDER MOST CIRCUMSTANCES WILL PROVIDE COMFORTABLE SHELTER AGAINST THE ELEMENTS. THERE ARE HOWEVER EXTREMES OF WEATHER FOR WHICH ALLOWANCES SHOULD BE MADE.

DO NOT BLAME THE TENT!

ERECTING YOUR TENT

PLEASE NOTE THE INDIANA 8 IS A LARGE FAMILY TENT AND WE STRONGLY RECOMMEND IT IS ERECTED BY A MINIMUM OF TWO ADULTS.

1: REMOVE THE CONTENTS OF THE CARRY BAG AND IDENTIFY ALL THE COMPONENT PARTS.

- INNER TENT
- FLYSHEET
- POLE BAG AND CONTENTS
- PEG BAG AND CONTENTS

2: SELECT A SITE THAT IS CLEAR OF ANY SHARP OBJECTS, STICKS AND STONES E.T.C

3: IN THE POLE BAG, THERE SHOULD BE FOUR SETS OF SHOCKCORDED FIBERGLASS POLES, ALL OF EQUAL LENGTH, TWO SETS OF STEEL SIDE SUPPORT POLES AND TWO SETS OF STEEL CANOPY POLES. THE SIDE SUPPORT POLES WILL HAVE A FLATTENED END ON EACH END OF EACH POLE SET & THE CANOPY POLES WILL HAVE SHORT SPIKES ON ONE END OF EACH POLE SET.

ASSEMBLE ALL THE POLES AND LAY OUT ON THE GROUND WHERE THEY ARE EASILY ACCESSIBLE.

4: UNFOLD THE FLYSHEET AND SPREAD OUT ON THE FLOOR SO YOU ARE ABLE TO SEE THE FOUR SLEEVE SECTIONS OF THE ROOF. AT THIS POINT CHECK THAT THE MOVEABLE FRONT DOOR PANEL IS ZIPPED INTO THE FRONT END OF THE TENT AND NOT THE SECONDARY INTERNAL POSITION.

TAKING ANY SHOCKCORDED FIBERGLASS MAIN POLE, THREAD THE POLE THROUGH THE SLEEVE SECTIONS SO THERE IS AN EQUAL LENGTH OF POLE PROTRUDING FROM EITHER SIDE OF THE SLEEVE ENDS.

ONCE THE POLE IS THREADED INTO PLACE CHOOSE ONE END OF THE POLE AND ENGAGE THE END FERRULE INTO THE POLE RETAINING FIXTURE OR EYELET. THIS WILL BE LOCATED AT THE BASE OF THE FLYSHEET, NEAR TO THE SEAM RUNNING DOWN FROM THE SLEEVE, IN WHICH THE POLE IS LOCATED. EACH POLE RETAINING

FIXTURE WILL HAVE A METAL RING WITH ONE OR MORE RETAINING PINS ATTACHED TO IT (DEPENDANT UPON MODEL) THE RETAINING PIN IS DESIGNED TO SLIDE UP INSIDE THE POLE ENDS THUS SECURING THE POLE INTO PLACE.

FROM THE OPPOSITE END OF THE SAME POLE CAREFULLY PUSH THE REMAINING POLE THROUGH THE SLEEVES SO IT ASSUMES A SEMI-CIRCULAR SHAPE. WHEN THE END FERRULE IS LEVEL TO THE POLE RETAINING FIXTURE OR EYELET ON THIS SIDE, ENGAGE IT INTO PLACE AS BEFORE. PLEASE NOTE ON SOME MODELS THERE MAY BE AN ADJUSTABLE WEBBING LOOP CONNECTING THE RING TO THE BASE OF THE FLYSHEET. THIS LOOP SHOULD BE OPENED UP TO ITS FULL LENGTH WHILE ENGAGING THE PIN ON THE RING INTO THE POLE END. ONCE THE PIN IS INSERTED THE WEBBING LOOP CAN BE TIGHTENED SO THE POLE IS FIRMLY LOCKED INTO THE POLE END.

ENSURE CARE IS TAKEN DURING THIS PROCEDURE, NOT TO ALLOW THE ENDS OF THE SHOCKCORDED POLES TO DAMAGE SLEEVES OR FLYSHEET MATERIAL.

5: TAKING THE SECOND, THIRD & FORTH REMAINING POLES SEPARATELY REPEAT POINT 4. IT IS BEST TO START AT ONE END OF THE FLYSHEET AND WORK TOWARDS THE OPPOSITE END OF THE TENT, ALL THE SHOCKCORDED FIBREGLASS POLES ARE THE SAME LENGTH SO ANY POLE CAN FIT INTO ANY ROOF SLEEVE.

DURING BOTH POINTS 4 & 5 ENSURE THAT THE POLE JOINING FERRULES DO NOT CATCH ON THE INSIDE OR EDGE OF THE MATERIAL SLEEVES. SHOULD THIS HAPPEN CAREFULLY FREE THE SLEEVE BEFORE CONTINUING. FAILURE TO FREE THE SLEEVE MAY CAUSE THE MATERIAL TO TEAR AND OR STITCHED SEAMS TO BURST

6: THE FLYSHEET SHOULD NOW BE READY FOR PEGGING. POSITION THE FLYSHEET ON THE GROUND SO THAT THE BEDROOM END IS FACING INTO THE PREVAILING WIND. CLOSE ALL ZIPS ON THE FLYSHEET AND USING THE PEGS PROVIDED PEG THE MAIN TWO CORNERS OF THE END THAT'S FACING INTO THE WIND, TO THE GROUND. TAKE THE TWO MAIN PEGGING POINTS ON THE OPPOSITE END AND PULL THE FLYSHEET AND POLES AWAY FROM THE PEGGED SECTION SO THE TENT TAKES SHAPE, THEN PEG THESE POINTS TO THE GROUND. ASSISTANCE FROM THE SECOND PERSON PRESENT WILL BE REQUIRED AT THIS POINT.

ENSURE THAT THE OVERALL LAY OF THE FLYSHEET IS SMOOTH WHEN PEGGED. THE FLYSHEET SHOULD BE TAUGHT, BUT NOT OVER-TENSIONED, AS THIS WILL ONLY DISTORT THE FIBERGLASS / METAL POLES AND SUBSEQUENTLY AFFECT STABILITY. YOU MAY FIND IT NECESSARY TO ADJUST THE POSITION OF THE TWO END PEGGING POINTS IN ORDER TO GET THE OVERALL LAY OF THE FLYSHEET FABRIC SMOOTH AND FREE FROM WRINKLES OR FOLDS.

ONCE YOU ARE SATISFIED WITH THE OVERALL LAY OF THE FLYSHEET YOU CAN THEN AND ONLY THEN PEG THE REMAINING PEGGING LOOPS INTO POSITION.

TAKE ONE OF THE TWO SIDE SUPPORT POLES. ON EACH END OF THE POLE YOU WILL SEE A FLATTENED 'SPADE' SECTION. THIS FLATTENED SECTION IS DESIGNED TO FIT INTO REINFORCED WEBBING POCKETS ON THE SIDE PANELS AT EACH END OF THE TENT. FROM THE FRONT DOOR END OF THE TENT SLIDE THE POLE THROUGH THE SMALL HOLE IN THE TOP CORNER OF THE INTERNAL DOOR POSITION ZIP GUSSET AND GUIDE THE POLE TOWARDS THE BACK OF THE TENT ENGAGING THE 'SPADE' END INTO THE REINFORCED WEBBING POCKET AT THE REAR OF THE TENT. USING THE ADJUSTMENT CLAMP ON THE POLE ADJUST THE LENGTH ACCORDINGLY SO THE OPPOSITE 'SPADE' END OF THE POLE CAN BE LOCATED INTO THE REINFORCED WEBBING POCKET AT THE FRONT END OF THE TENT ON THE SAME SIDE. ONCE THE TWO 'SPADE' ENDS ARE LOCATED FIRMLY, TIGHTEN THE ADJUSTMENT CLAMP SO THE POLE IS SECURELY FIXED INTO POSITION. REPEAT THIS WITH THE REMAINING SIDE SUPPORT POLE ON THE OPPOSITE SIDE OF THE TENT.

ATTACH ALL THE GUY ROPES TO ALL THE GUYING POINTS AND PEG SECURELY, AT A SUITABLE DISTANCE FROM THE TENT. TRY NOT TO PEG TOO CLOSE TO THE TENT AS THIS WILL NOT GIVE ADEQUATE SUPPORT AND MAY CAUSE THE FABRIC UNDER THE GUY POINT ITSELF TO BECOME BAGGY OR LOOSE THUS ALLOWING INNER AND OUTER TO TOUCH.

THE FRONT AND REAR GUY POINTS SHOULD BE ADEQUATELY TENSIONED TO PREVENT THE POOLING OF WATER ON THE INDIVIDUAL ROOF SECTIONS. ONCE THE GUY ROPES HAVE BEEN PEGGED PLEASE CHECK BOTH THE SIDE SUPPORT POLES AS THEY MAY NEED ADJUSTING IN LENGTH AGAIN. THE TENSION ON THE GUY ROPES MAY HAVE MOVED THE REINFORCED WEBBING POCKETS IN RELATION TO THE SIDE SUPPORT POLE LENGTH. SIMPLY UNDO THE ADJUSTMENT CLAMP, EXTEND THE POLE UNTIL THE SPADE ENDS FIT SECURELY INTO THE REINFORCED WEBBING POCKETS AT EACH END OF THE TENT AND TIGHTEN THE ADJUSTMENT CLAMP.

*THE PEGS PROVIDED WITH THIS TENT ARE STANDARD PEGS, SUITABLE FOR MOST TERRAIN'S. HOWEVER THERE WILL BE OCCASIONS WHEN THE GROUND MAY BE FAR TOO HARD OR ROCKY AND EQUALLY TOO BOGGY OR SANDY. IN THIS INSTANCE SPECIALIST PEGS CAN BE PURCHASED THROUGH YOUR LOCAL RETAILER AND **SHOULD** BE USED*

7: UNFOLD THE GROUNDSHEET OF THE TENT AND CLIP INTO POSITION. PLEASE NOTE THE POSITION OF THE PEGGING COWLS ON THE GROUNDSHEET. THESE ARE HOLES IN THE GROUNDSHEET WITH A FABRIC SKIRT SEWN AROUND THE EDGE WITH A DRAW STRING CLOSURE ON THE TOP EDGE. THESE ARE DESIGNED TO ALLOW THE INNER TENT TO BE PEGGED DOWN TO THE GROUND THROUGH THE COWL AND THE FABRIC SKIRT CAN THEN BE CLOSED AND DRAWN UP AROUND THE INNER TENT PEGGING POINT. PLEASE ENSURE THAT THE GROUNDSHEET IS CLIPPED IN THE CORRECT WAY ROUND SO THE PEGGING COWLS FOR THE INNER TENT ARE AT THE CORRECT END OF THE TENT. THERE WILL ALSO BE PEGGING COWLS FOR THE SECONDARY FRONT DOOR PANEL POSITION. THERE WILL ONLY BE 2 PEGGING COWLS FOR THE INNER TENT SO THIS END OF THE GROUNDSHEET SHOULD BE POSITIONED TOWARDS THE REAR OF THE TENT.

UNFOLD THE INNER TENT AND PLACE IT INSIDE THE FLYSHEET BEDROOM AREA WITH THE DOOR FACING TOWARDS THE INSIDE OF THE TENT AND ON TOP OF THE GROUNDSHEET YOU HAVE ALREADY CLIPPED IN. THE INNER TENT WILL HAVE LOOPS AND HOOKS ON THE BASE AND SIMPLY CLIPS INTO POSITION. ALONG THE FRONT EDGE OF THE INNER TENT YOU WILL SEE WEBBING LOOPS, WHICH ARE SEWN INTO THE INNER TENT AT THE SAME POSITION AS THE PEGGING COWLS IN THE GROUNDSHEET. SIMPLY PEG THE INNER TENT DOWN TO THE GROUND THROUGH THE PEGGING COWLS AND THEN TIGHTEN AND CLOSE THE PEGGING COWL AROUND THE WEBBING LOOP OF THE INNER TENT WITH THE DRAW STRING CLOSURE PROVIDED ON THE TOP OF THE GROUNDSHEET PEGGING COWL ITSELF.

AN ELASTIC TOGGLE AND RING SYSTEM SUSPEND THE INNER TENT FROM THE INSIDE OF THE FLYSHEET. THE ELASTIC LOOPS AND TOGGLES ARE FOUND ON THE INNER TENT WHILE THE SUSPENSION LOOPS AND RINGS ARE FOUND ON THE FLYSHEET.

THE ELASTIC LOOPS AND TOGGLES SHOULD BE SIMPLY FED THROUGH THE CORRESPONDING LOOPS AND RINGS ON THE FLYSHEET. OPEN THE DOOR OF THE INNER TENT KNEEL OR CAREFULLY STAND ON THE GROUNDSHEET STARTING AT THE BACK CONNECT ALL THE LOOPS AND RINGS ON THE REAR POLE SECTION WORK FORWARD UNTIL THE INNER IS COMPLETELY SUSPENDED.

THERE WILL ALSO BE TWO ADJUSTABLE WEBBING FAST BUCKLES IN LINE WITH THE POCKETS ON THE INNER TENT FRONT PANEL. LOCATE THE MALE AND FEMALE SECTIONS OF THE FAST BUCKLE TOGETHER AND PUSH CLOSED UNTIL THE BUCKLE LOCKS THE WEBBING CAN BE ADJUSTED IN LENGTH TO ADD SUPPORT TO THE INNER TENT IN THIS AREA. PLEASE NOTE THE TOTAL WEIGHT LOADING OF ALL POCKETS ON THE FRONT OF THE INNER TENT SHOULD NOT EXCEED 3 KGS

YOUR TENT IS NOW READY FOR USE, ENJOY YOUR HOLIDAY.

THE SETS OF UPRIGHT CANOPY POLES PROVIDED WILL ALLOW EITHER THE FRONT OR BACK DOORS TO BE ERECTED AS A SUN CANOPY IF SO DESIRED.

AS WEATHER CONDITIONS CAN CHANGE BOTH DRAMATICALLY AND QUICKLY WE RECOMMEND THAT YOU PITCH YOUR TENT READY TO ACCEPT ANY INCLEMENT WEATHER CONDITIONS. THE FRONT AND OR SIDE DOOR CANOPIES SHOULD NOT BE LEFT UP OVERNIGHT OR WHILST THE TENT IS UNATTENDED. GUY LINES ARE ATTACHED TO YOUR TENT AND SHOULD BE USED AT ALL TIMES.

TAKING YOUR TENT DOWN

STRIKING CAMP IS BASICALLY A COMPLETE REVERSAL OF THE ERECTION PROCEDURE.

CARE SHOULD BE TAKEN WHEN RELEASING SHOCKCORDED POLES FROM THEIR MOUNTINGS AS THE TENSION IN THE POLE CAN CAUSE DAMAGE OR INJURY IF THE POLE IS NOT DISMANTLED IN A CONTROLLED MANNER.

IT IS ALWAYS EASIER TO PUSH SHOCKCORDED POLES THROUGH AND OUT OF THE SLEEVES RATHER THAN TO TRY AND PULL THEM THROUGH. AGAIN TAKE CARE NOT TO DAMAGE THE SLEEVES WITH THE POLE ENDS OR FERRULES WHILST REMOVING THEM FROM THE FLYSHEET.

IT IS ALWAYS BETTER TO STRIKE CAMP WHEN YOUR TENT IS COMPLETELY DRY, HOWEVER THIS IS NOT ALWAYS POSSIBLE.

SHOULD YOU HAVE TO TAKE YOUR TENT DOWN WET, THEN IT IS IMPERATIVE THAT IT IS DRIED OUT COMPLETELY WITHIN 24 HOURS. ***A WET TENT WILL GO MOULDY CAUSING IRREPARABLE DAMAGE TO COTTON COMPONENTS.***

FOLDING YOUR TENT

1: IN ORDER TO MAKE A NEAT AND TIDY PACKAGE, THAT WILL FIT EASILY INTO THE OUTER BAG, ALWAYS HAVE THE OUTER BAG CLOSE AT HAND WHILST YOU ARE FOLDING THE TENT UP.

2: IT IS BETTER TO FOLD THE FLYSHEET UP FIRST, INTO A LONG RECTANGLE. MAKE THE RECTANGLE APPROXIMATELY 10 CMS SHORTER IN WIDTH THAN THE OUTER BAG.

3: AFTER BRUSHING OR WIPING THE INNER TENT GROUND SHEET TO ENSURE IT IS CLEAN AND DRY, PLACE THE FLYSHEET ON TOP OF THE INNER TENT.

4: FOLD THE EDGES OF THE GROUND SHEET IN SO TO COVER THE FLYSHEET IN THE MIDDLE, MAKE SURE THAT THE OVERALL PACKAGE IS AGAIN ABOUT 10 CMS SHORTER IN WIDTH THAN THE OUTER BAG.

5: ROLL THE PACKAGE UP, ROLLING TOWARDS THE DOOR END OF THE INNER TENT IN ORDER TO ALLOW TRAPPED AIR TO ESCAPE.

WHEN YOU HAVE ROLLED THE PACKAGE UP SECURE IT WITH THE ORIGINAL TIE TAPES SUPPLIED.